

ORCHESTRATE

PORTABLE INTERVIEW

INSTANT INTERVIEW

PORTABLE ◀ FLEXIBLE ▶ ACCESSIBLE

INTRODUCING THE NEXT GENERATION OF PORTABLE KITS



- ▶ Conduct an **Interview** anytime, anywhere*
- ▶ Eliminate latency in memory recall, cold feet/second thoughts and interference
- ▶ No more **Interview** room negotiations with other agencies
- ▶ Own and instantly share your **Interview***
- ▶ Maintain protected "chain of custody"*

- ▶ Travel with ease: Lightweight carry on
- ▶ Self-contained, military grade, lockable unit
- ▶ Set up and take down in minutes
- ▶ Secured system to prevent tampering*
- ▶ Uses a leading brand of cameras and data-gathering devices
- ▶ Open Platform: Integrate with existing backend software*

KEY FEATURES

AXIS M5065 COMPACT PTZ CAMERA

Pan, tilt, zoom with 5x optical zoom and 10x digital zoom, Autofocus, 1080p/ 2MP
Built-in microphone, 0 to 4z5 °C Operating Temperatures, 1.2 lux Light Sensitivity (Color)

AXIS M1135 NETWORK CAMERA

HDTV 2MP compact/flexible design, Built-in microphone with auto gain , 0.1 lux Light Sensitivity, (Color), 0.02 lux Light Sensitivity (B/W), -20 to 50 °C Operating Temperatures

MANFROTTO MINI TRIPOD

Mini tripod two leg angles give you stability on uneven ground, Camera tilts to a full 90°

COMPUTER & ACCESSORIES LID ORGANIZER

Dimensions of computer pouch 15.40" x 11.10" x 1.70"

PELICAN AIR 1535 CASE

Maximum airline carry on size, Super-light proprietary HPX²™ Polymer, Quiet Rolling Stainless-Steel Bearing Wheels

BRING YOUR OWN DEVICE

The software runs on Windows 10 or higher so no need to invest in a new laptop.

SECURE HARDWARE DESIGN

System security prevents tampering from unauthorized individuals

SPECIFICATIONS

TAMPER-PROOF TECHNOLOGY	SHA-2 hashing algorithm and chain of custody including standard reports
VIDEO ENCODING	H.264 baseline and main profile (MPEG-4 part 10/AVC), streaming compliant
CAMERA SECURITY	HTTPS encrypted communication to the camera, IEEE 802.1x network access control
SUPPORTED PROTOCOLS	IPv4/v6, FTP, CIFS/SMB, SMTP, Bonjour, UPnP, ONVIF
POE SUPPORT	5-Port Gigabit Switch with 4-Port PoE, IEEE 802.3af compliant
USE YOUR OWN CAMERAS	Support for a third or fourth camera via POE
POWER	Standard C13 Universal Power Cord (NEMA) providing power to all components
CASE SPECIFICATIONS	21.96" X 11.97" X 8.98", Weight with equipment is 16.8 lbs.